



## PRESTONE PROCLEAN INTERIOR CLEANER

MSDSP376

### SECTION 1: IDENTIFICATION

PRODUCT NAME: PRESTONE PROCLEAN INTERIOR & CARPET CLEANER  
AS345 Formula: B4293

MANUFACTURER: Prestone Products Corporation  
39 Old Ridgebury Road  
Danbury, CT 06810-5109

INFORMATION PHONE NUMBER: (203) 830-7800

EMERGENCY PHONE NUMBER: CHEMTREC 1-800-424-9300  
483-7161 in the District of Columbia

MSDS DATE OF PREPARATION/REVISION: 04/15/98

### SECTION 2: PRODUCT COMPONENTS

HAZARDOUS COMPONENTS	CAS#	PERCENT	EXPOSURE LIMITS
2-Butoxyethanol	111-76-2	1-10	50 ppm TWA skin OSHA PEL 25 ppm TWA skin ACGIH TLV
Propane/Isobutane Propellant	74-98-6 75-28-5	<6	1000 ppm PEL TWA Asphyxiant ACGIH TLV
Non-ionic Surfactant	9002-93-1	<3	None Established
Sodium Metasilicate pentahydrate	10213-79-3	<3	None Established

NON-HAZARDOUS INGREDIENTS >1%  
Water 7732-18-5

### SECTION 3: HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

Flammable Aerosol: Heated can may rupture. Eye and skin irritant.  
Inhalation may cause headache, dizziness and drowsiness. Deliberate  
concentration and inhalation of vapors may be fatal.

#### POTENTIAL HEALTH EFFECTS:

##### ACUTE HAZARDS:

**INHALATION:** Breathing vapors or mists may cause mild irritation of the mucous membranes, headache, dizziness and drowsiness.

**SKIN CONTACT:** May cause mild irritation and defatting of the skin.

**SKIN ABSORPTION:** Prolonged, extensive skin contact may cause absorption of 2-butoxyethanol in harmful amounts.

**EYE CONTACT:** May cause mild irritation.

**INGESTION:** May cause gastrointestinal irritation and nausea. Large amounts swallowed may cause pulmonary edema, acidosis, hypotension and renal (kidney) injury.

**CHRONIC HAZARDS:** Prolonged overexposure to 2-butoxyethanol may cause blood, liver and kidney damage. Prolonged skin exposure may cause

**PRESTONE PROCLEAN INTERIOR CLEANER****MSDSP37**

dermatitis.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** The skin irritating properties of this product may aggravate an existing skin condition, e.g. eczema.

**CARCINOGEN:** None of the components of this product are listed as a carcinogen or suspected carcinogen by IARC, NTP or OSHA.

**SECTION 4: FIRST AID MEASURES**

**INHALATION:** If symptoms of exposure occur, remove to fresh air and seek medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Wash all affected and exposed areas with soap and water. If irritation or redness occurs and persists, seek medical attention.

**EYE CONTACT:** Exposed eyes should be immediately flushed with copious amounts of water using a steady stream for a minimum of 15 minutes. If irritation, pain, swelling or tearing develop seek immediate medical attention.

**INGESTION:** Ingestion is an unlikely route of exposure for aerosol products. If ingestion occurs rinse mouth with a small amount of water. Immediately call local poison control center or go to an emergency department. Never give anything by mouth to an unconscious or drowsy person.

**NOTES TO PHYSICIAN:** There is no specific antidote. Treatment should be directed at the control of symptoms and the clinical condition. Closely monitor acid-base, fluid and electrolyte status. The role of ethanol therapy in preventing ethylene glycol butyl ether toxicity is uncertain. The poison center should be consulted on these cases.

**SECTION 5: FIRE AND EXPLOSION DATA**

**FLASH POINT:** <-20 F (-28 C) TCC

**AEROSOL FIRE PROTECTION LEVEL:** Level 1 (NFPA 30B)

**AEROSOL FLAME EXTENSION:**

**AUTOIGNITION TEMPERATURE:** Not Determined

**FLAMMABILITY LIMITS:** LEL: 1.9 (propellant) UEL: 8.5% (propellant)

**EXTINGUISHING MEDIA:** Use water fog, carbon dioxide, universal foam or dry chemical. Cool fire exposed containers with water.

**SPECIAL FIRE FIGHTING PROCEDURES:** Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored. Protect against rupturing cans.

**UNUSUAL FIRE HAZARDS:** Flammable aerosol. Aerosol cans may burst in the heat of fire.

**HAZARDOUS COMBUSTION PRODUCTS:** Burning may produce carbon monoxide and carbon dioxide.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

Eliminate all ignition sources. Ventilate area. Wear appropriate protective clothing and equipment (See Section 8). Collect with



## PRESTONE PROCLEAN INTERIOR CLEANER

MSDSP376

absorbent material and place in appropriate, labeled container for disposal.

### SECTION 7: HANDLING AND STORAGE

Avoid eye and skin contact.  
 Avoid breathing vapors or mists.  
 Use only with adequate ventilation.  
 Wash exposed skin thoroughly with soap and water after use.  
**Flammable Aerosol!**  
 Keep container away from heat, sparks, open flames and all other sources of ignition.  
 Do not smoke during use or until product is dry and vapors have dissipated.  
 Store product below 120 F and away from direct sunlight.  
 Store in a well ventilated area.  
 Do not puncture or incinerate containers.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**VENTILATION:** Use general ventilation or local exhaust as required to maintain exposures below the occupational exposure limits.

**RESPIRATORY PROTECTION:** None usually required for normal, consumer use. Where concentrations may exceed the exposure limits a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**GLOVES:** Chemical resistant gloves such as butyl rubber where contact is possible.

**EYE PROTECTION:** Safety glass or goggles.

**OTHER PROTECTIVE EQUIPMENT/CLOTHING:** Appropriate protective clothing as needed to minimize skin contact.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE AND ODOR:** Clear to slightly hazy liquid with citrus odor packaged as an aerosol product.

<b>pH:</b> 12.5	<b>SPECIFIC GRAVITY:</b> 1.0 g/mL
<b>BOILING POINT (F):</b> Not determined	<b>VAPOR PRESSURE:</b> 45 PSIG @ 70 F
<b>MELTING POINT (F):</b> Not applicable	<b>VAPOR DENSITY:</b> 4.0
<b>SOLUBILITY IN WATER:</b> Soluble	<b>EVAPORATION RATE:</b> less than 1 (Butyl Acetate=1)
<b>PERCENT VOLATILE:</b> >98%	<b>VISCOSITY:</b> Not determined

### SECTION 10: STABILITY AND REACTIVITY

**STABILITY:** Stable  
**CONDITIONS TO AVOID:** Heat, sparks, flames and all other sources of ignition.  
**INCOMPATIBILITY:** Strong oxidizing agents.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide.  
**HAZARDOUS POLYMERIZATION:** Will not occur  
**CONDITIONS TO AVOID:** None known.



PRESTONE PROCLEAN INTERIOR CLEANER

MSDSP376

SECTION 11: TOXICOLOGICAL INFORMATION

2-Butoxyethanol: LD50 Oral Rat: 470 mg/kg
LC50 Inhalation Rat: 700 ppm/7 hr
LD50 Skin Rabbit: 220 mg/kg

Non-ionic Surfactant: No toxicity data available

Sodium Metasilicate: LD50 Oral Rat: 800 mg/kg

Propane: No toxicity data available

Isobutane: LC50 Inhalation Rat: 1041 gm/m3/2 hr

SECTION 12: ECOLOGICAL INFORMATION

No ecotoxicity data is available for this product or its components at this time.

SECTION 13: DISPOSAL INFORMATION

Dispose of product as hazardous waste (ignitable) in accordance with all local, state/provincial and federal regulations.

Do not incinerate container.

SECTION 14: TRANSPORT INFORMATION

U.S. DOT HAZARD CLASSIFICATION

PROPER SHIPPING NAME: CONSUMER COMMODITY
TECHNICAL NAME: NONE
UN NUMBER: NONE
HAZARD CLASS/PACKING GROUP: ORM-D
LABELS/PLACARDS REQUIRED: NONE

MARINE POLLUTANTS: This product does not contain Marine Pollutants defined in 49 CFR 171.8.

IMDG CODE SHIPPING CLASSIFICATION

DESCRIPTION: AEROSOLS, CLASS 2, UN 1950, FP -29C, LTD. QTY.
ID NUMBER: UN1950
HAZARD CLASS: 2
PACKING GROUP: NONE
LABELS REQUIRED: NONE- Aerosol Markings, On all four sides.
PLACARDS REQUIRED: Limited Quantities on all four sides.
IMDG PG 2102

SECTION 15: REGULATORY INFORMATION

SARA 311/312 HAZARD CLASSIFICATION: Acute health, chronic health, fire hazard, sudden release of pressure

SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):
2-Butoxyethanol 111-76-2 10% maximum (glycol ether)



PRESTONE PROCLEAN INTERIOR CLEANER

MSDSP376

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: This product is not subject to spill reporting requirements under CERCLA, however, many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65 - This product does not contain chemicals regulated under California Proposition 65.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

CANADIAN WEMIS CLASSIFICATION: Class D - Division 2 - Subdivision B - (A toxic material causing other chronic effects), Class B - Division 5 (Flammable Aerosol)

EUROPEAN INVENTORY OF EXISTING COMMERCIAL CHEMICAL SUBSTANCES

(EINECS) : All of the ingredients are listed on the EINECS inventory.

AUSTRALIA: All of the ingredients of this product are listed on the Australian Inventory of Chemical Substances.

SECTION 16: OTHER INFORMATION

NFPA RATING (NFPA 704) - FIRE: 4  
HEALTH: 2  
REACTIVITY: 0

This MSDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact:  
Stan Prusakowski  
Prestone Products Corporation  
39 Old Ridgeway Road  
Danbury, CT 06810-5109  
(203)830-7865

**Prestone**<sup>®</sup>  
**PRODUCTS CORPORATION**

**PRESTONE BUG & TAR REMOVER**

**MSDSP369**

**SECTION 1: IDENTIFICATION**

PRODUCT NAME: PRESTONE Bug & Tar Remover  
 AS355 Formula: TM-4603

MANUFACTURER: Prestone Products Corporation  
 39 Old Ridgebury Road  
 Danbury, CT 06810-5109

INFORMATION PHONE NUMBER: (203) 830-7800

EMERGENCY PHONE NUMBER: CHEMTREC 1-800-424-9300  
 483-7161 in the District of Columbia

PostNet  
 Fax Note R7673  
 To: *Cliff*  
 Fax: 800-739-8139  
 From: *Dege*  
 Phone#: 1-800-662-7737 x783

Date: 6/16/98 # of pages: 5

MSDS DATE OF PREPARATION/REVISION: 06/19/97

**SECTION 2: PRODUCT COMPONENTS**

HAZARDOUS COMPONENTS	CAS#	PERCENT	EXPOSURE LIMITS
Mineral Spirits	8052-41-3	20-30	500 ppm TWA OSHA PEL 100 ppm TWA ACGIH TLV
Ethyl Benzene	100-20-7	<2	100 ppm TWA OSHA PEL 100 ppm TWA ACGIH TLV
Xylene	1330-20-7	1-5	100 ppm TWA OSHA PEL 100 ppm TWA ACGIH TLV
ropane-Isobutane-	74-98-6	10-20	1000 ppm TWA OSHA PEL
n-Butane Propellant	75-28-5 106-97-8		800 ppm TWA ACGIH TLV

Non-Hazardous Components >1%  
 Water 7732-18-5 50-60%

**SECTION 3: HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

Flammable Aerosol! Heated can may rupture. Eye and skin irritant.  
 Inhalation may cause headache, dizziness, drowsiness, nausea,  
 narcosis and unconsciousness. Deliberate concentration and  
 inhalation of vapors may be fatal.

**POTENTIAL HEALTH EFFECTS:**

**ACUTE HAZARDS:**

**INHALATION:** Inhalation of high concentrations may produce central nervous system effects including headache, dizziness, fainting, tremor, incoordination, hallucinations, lowered body temperature, muscular weakness, metabolic acidosis, depressed respiration and heart rate, heart rhythm irregularities, shortness of breath, coma, death.

**SKIN CONTACT:** May cause irritation, seen as localized reddening and swelling. Product may be absorbed through the skin in toxic amounts if exposure is prolonged or repeated causing toxic effects.

**EYE CONTACT:** Liquid or vapors may be irritating and cause pain, tearing, reddening and swelling accompanied by a stinging sensation.

**INGESTION:** This is an unlikely route of exposure with an aerosol product. Swallowing large amounts may cause central nervous system depression, high blood sugar, acidosis, liver and kidney damage. May cause irritation of the mouth, esophagus and stomach resulting in nausea, vomiting and diarrhea. Aspiration into the lungs may occur during ingestion or vomiting, resulting in injury.

**PRESTONE BUG & TAR REMOVER****MSDSP369**

**CHRONIC HAZARDS:** Reports have associated repeated and prolonged overexposure to petroleum distillates with adverse liver, kidney and bone marrow effects with permanent brain and nervous system damage.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:** Because of its irritating defatting properties, this material may aggravate an existing skin condition. Individuals with preexisting diseases of the heart or central nervous system may have increased susceptibility to the toxicity of excessive exposure to the product's propellant.

**CARCINOGEN:** None of the components is listed as a carcinogen or potential carcinogen by IARC, NTP or OSHA.

**SECTION 4: FIRST AID MEASURES**

**INHALATION:** If symptoms of exposure develop, remove to fresh air. If breathing becomes difficult, administer oxygen. Administer artificial respiration if breathing has stopped. Seek immediate medical attention.

**SKIN CONTACT:** Remove contaminated clothing. Wash all affected and exposed areas with soap and water. If irritation or redness persists, seek medical attention.

**EYE CONTACT:** Exposed eyes should be immediately flushed with copious amounts of water using a steady stream for a minimum of 15 minutes. If irritation, pain, swelling or tearing persist, seek medical attention.

**INGESTION:** Unlikely route of exposure with an aerosol container. Get immediate medical attention by calling a physician, Poison Control Center or hospital emergency room. If medical advice cannot be obtained, then take the person and product to the nearest medical emergency treatment center or hospital. Rinse mouth out with water. Do not induce vomiting. Never give anything by mouth who is unconscious or drowsy.

**NOTES TO PHYSICIAN:** There is no specific antidote. Treatment should be directed at the control of symptoms and clinical conditions. A serious potential toxic effect is aspiration pneumonitis, which may lead to non-cardiogenic pulmonary edema. The patient should be observed for signs of lung injury if aspiration is suspected and should be followed for delayed effects. Following excessive inhalation exposure, cardiac function should be monitored. Because of possible cardiac sensitization to catecholamines, drugs, such as epinephrine, should be used with special caution only in situations of emergency life support. Ethyl benzene does not appear to cause damage to the hematopoietic system in spite of its chemical similarity to benzene.

**SECTION 5: FIRE AND EXPLOSION DATA**

**FLASH POINT:** -123 F TCC

**AEROSOL FIRE PROTECTION LEVEL:** Level 2 (NFPA 30B)

**AEROSOL FLAME EXTENSION:** Not Determined

**AUTOIGNITION TEMPERATURE:** Not Determined

**FLAMMABILITY LIMITS:** LEL: 1.0% (Xylene) UEL: 7.0% (Xylene)  
2.1% (Propane) 9.5% (Propane)

**EXTINGUISHING MEDIA:** Use water fog, carbon dioxide, or dry chemical. Cool fire exposed containers with water.



## PRESTONE BUG & TAR REMOVER

MSDSP369

**SPECIAL FIRE FIGHTING PROCEDURES:** Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing for fires in areas where chemicals are used or stored. Protect against rupturing cans.

**UNUSUAL FIRE HAZARDS:** Very flammable aerosol. Aerosol cans may burst in the heat of fire.

**HAZARDOUS COMBUSTION PRODUCTS:** Burning may produce carbon dioxide and water.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

Eliminate all ignition sources. Ventilate area. Wear appropriate protective clothing and equipment (See Section 8). Collect with absorbent material and place in appropriate, labeled container for hazardous waste disposal.

### SECTION 7: HANDLING AND STORAGE

Avoid eye and skin contact.

Avoid breathing vapors or mists.

Use only with adequate ventilation.

Wash exposed skin thoroughly with soap and water after use.

**Flammable Aerosol!**

Keep container away from heat, sparks, open flames and all other sources of ignition.

Do not smoke during use or until product is dry and vapors have dissipated.

Store product below 120 F.

Store in a well ventilated area.

Do not puncture or incinerate containers.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

**VENTILATION:** Use local exhaust as required to maintain exposures below the occupational exposure limits.

**RESPIRATORY PROTECTION:** None usually required for normal, consumer use. Where concentrations are excessive and irritation develops, a NIOSH approved respirator with organic vapor cartridges and dust/mist prefilters or supplied air respirator is recommended. Equipment selection depends on contaminant type and concentration. Select and use in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**GLOVES:** Chemical resistant gloves such as Viton where contact is possible.

**EYE PROTECTION:** Splash-proof goggles.

**OTHER PROTECTIVE EQUIPMENT/CLOTHING:** Appropriate protective clothing as needed to minimize skin contact.

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

**APPEARANCE AND ODOR:** Cloudy liquid with citrus odor.

**pH:** 10.9

**BOILING POINT (F):** 175-400 F

**MELTING POINT (F):** N/A

**SOLUBILITY IN WATER:** Partial

**PERCENT VOLATILE:** N/A

**SPECIFIC GRAVITY:** 0.8

**VAPOR PRESSURE:** 46 PSIG @ 70 F

**VAPOR DENSITY:** 4.0

**EVAPORATION RATE:** <1 (Butyl Acetate=1)

**VISCOSITY:** N/A



**PRESTONE BUG & TAR REMOVER**

MSDSP36

**SECTION 10: STABILITY AND REACTIVITY****STABILITY:** Stable**CONDITIONS TO AVOID:** Heat, sparks, flames and all other sources of ignition.**INCOMPATIBILITY:** Strong oxidizing agents.**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon dioxide and water.**HAZARDOUS POLYMERIZATION:** Will not occur**CONDITIONS TO AVOID:** None known.**SECTION 11: TOXICOLOGICAL INFORMATION****Mineral Spirits:** LD50 Oral Rat: >5 gm/kg  
LC50 Inhalation Rat: >5500 mg/m<sup>3</sup>/4 hr**Xylene:** LD50 Oral Rat: 4300 mg/kg  
LD50 Skin Rabbit: >1700 mg/kg  
LC50 Inhalation Rat: 5000 ppm/4 hr**Propane:** No data available**Isobutane:** LC50 Inhalation Rat: 1041 gm/m<sup>3</sup>/2 hr**n-Butane:** LC50 Inhalation Rat: 648 gm/m<sup>3</sup>/4 hr**SECTION 12: ECOLOGICAL INFORMATION****Xylene:** LC50 Rainbow Trout 13.5 mg/L/96 hr  
LC50 Flathead Minnow 13.5 mg/L/96 hr**SECTION 13: DISPOSAL INFORMATION**

Dispose of product as hazardous waste (ignitable) in accordance with all local, state/provincial and federal regulations.  
Do not incinerate container.

**SECTION 14: TRANSPORT INFORMATION****U.S. DOT HAZARD CLASSIFICATION****PROPER SHIPPING NAME:** CONSUMER COMMODITY**TECHNICAL NAME:** NONE**UN NUMBER:** NONE**HAZARD CLASS/PACKING GROUP:** ORM-D**LABELS REQUIRED:** NONE**DOT MARINE POLLUTANTS:** This product does not contain Marine Pollutants as defined in 49 CFR 171.8.**IMDG CODE SHIPPING CLASSIFICATION****DESCRIPTION:** AEROSOLS, CLASS 2, UN1950, FP -86C, LTD. QTY.**ID NUMBER:** UN1950**HAZARD CLASS:** 2**PACKING GROUP:** NONE**LABELS REQUIRED:** NONE- Aerosol Markings On Carton**PLACARDS REQUIRED:** Limited Quantity, on all four sides.**IMDG PG 2102****SECTION 15: REGULATORY INFORMATION****EPA SARA 311/312 HAZARD CLASSIFICATION:** Acute health, chronic health, fire hazard, sudden release of pressure



## PRESTONE BUG &amp; TAR REMOVER

MSDSP369

EPA SARA 313: This Product Contains the Following Chemicals Subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):

Ethyl Benzene	100-41-4	<2%
Xylene	1330-20-7	1-5%

PROTECTION OF STRATOSPHERIC OZONE: This product is not known to contain or to have been manufactured with ozone depleting substances as defined in 40 CFR Part 82, Appendix A to Subpart A.

CERCLA SECTION 103: Spills of this product over the RQ (reportable quantity) must be reported to the National Response Center. The RQ for the product, based on the RQ for Xylene (5% maximum) of 100 lbs, is 2,000 lbs. Many states have more stringent release reporting requirements. Report spills required under federal, state and local regulations.

CALIFORNIA PROPOSITION 65 - This product does not contain chemicals regulated under California Proposition 65.

EPA TSCA INVENTORY: All of the components of this material are listed on the Toxic Substances Control Act (TSCA) Chemical Substances Inventory.

CANADIAN ENVIRONMENTAL PROTECTION ACT: All of the ingredients are listed on the Canadian Domestic Substances List.

CANADIAN WHMIS CLASSIFICATION: Class D - Division 2 - Subdivision B - (Toxic material causing other chronic effects), Class B - Division 5 (Flammable Aerosol)

## SECTION 16: OTHER INFORMATION

NFPA RATING (NFPA 704) - FIRE: 4  
HEALTH: 2  
REACTIVITY: 0

This MSDS is directed to professional users and bulk handlers of the product. Consumer products are labeled in accordance with Federal Hazardous Substances Act regulations.

While Prestone Products Corporation believes that the data contained herein are factual and the opinions expressed are those of qualified experts regarding the results of tests conducted, the data are not to be taken as a warranty or representation for which Prestone Products Corporation assumes legal responsibility. They are offered for your consideration, investigation and verification. Any use of these data and information must be determined by the user to be in accordance with applicable federal, state and local laws and regulations.

If more information is needed, please contact: Stan Prusakowski  
Prestone Products Corporation  
39 Old Ridgebury Road  
Danbury, CT 06810-5109  
(203) 830-7865