



Material Safety Data Sheet

Product code 97400

Product name Industrial Protective Coating High Solids OSHA Blue

Revision Date 13-Sep-2006

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product code 97400
Product name Industrial Protective Coating High Solids OSHA Blue
Recommended Use Coating
Supplier Lawson Products, Inc.
1666 East Touhy Avenue
Des Plaines, IL 60018
(847)-827-9666
Emergency telephone number (888) 426-4851

2. HAZARDS IDENTIFICATION

Emergency Overview
Irritant. Extremely flammable.

Color Blue **Odor** Solvent **Form** Aerosol

Aggravated Medical Conditions Reports have associated prolonged overexposure to solvents with permanent brain and nervous system damage.

Principal Routes of Exposure Inhalation. Skin absorption. Eyes.

Potential health effects

Eyes Irritation. Swelling.
Skin Skin Irritation.
Inhalation Exposure to hot fumes may cause nausea and damage to respiratory system. May cause irritation of the nose and throat. Dizziness. Headaches. Fatigue. Central nervous system effects. Repeated or prolonged exposure may cause the following effects. Kidney damage. Liver damage. Damage to blood. Changes in heart rate. Misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.
Ingestion Irritating to mouth, throat and stomach.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Methyl Propyl Ketone	107-87-9	1-5
Acetone	67-64-1	10-30
Propane	74-98-6	10-30
N-Butane	106-97-8	5-10
Barium Sulfate	7727-43-7	5-10
Ethylene glycol monopropyl ether	2807-30-9	3-7
Methylisobutyl ketone	108-10-1	3-7
Titanium Dioxide	13463-67-7	1-5
Isobutyl acetate	110-19-0	1-5
Xylene (mix)	1330-20-7	1-5

4. FIRST AID MEASURES

Eye contact Remove to fresh air. Rinse thoroughly with plenty of water, also under the eyelids. Seek medical attention if irritation persists.
Skin contact Wash area thoroughly with soap and water. Remove and wash contaminated clothing before re-use.
Ingestion Call a physician or Poison Control Center immediately.
Inhalation Move to fresh air. Provide oxygen or artificial respiration if necessary. Keep warm and quiet. Consult a physician.

5. FIRE FIGHTING MEASURES

Flash point °C -19
Flash point °F -2
Method No information available

Autoignition temperature °C No data available
Autoignition temperature °F No data available

Flammability Limits (% in Air)
Upper 10.9
Lower 1.7

Specific Information for Aerosol Products

Flame extension 15"
Flashback None

Suitable extinguishing media
Carbon dioxide (CO₂). Water spray. Alcohol-resistant foam. Sand.

Special protective equipment for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear

Fire and Explosion Hazards
Extremely flammable liquid and vapor. Vapors of this product may develop a flammable atmosphere in confined areas. Firefighters should wear NIOSH/MSHA approved (or equivalent) self-contained pressure-demand breathing apparatus and full protective clothing.

Product code 97400

Product name Industrial Protective Coating High Solids
OSHA Blue

Sensitivity to shock
No information available.

Sensitivity to static discharge
Yes. Take precautionary measures against static discharges

6. ACCIDENTAL RELEASE MEASURES

Methods for cleaning up

Personnel should wear appropriate protective equipment. Follow all precautions for handling. Please refer to appropriate sections of MSDS for additional information. Evacuate area of unprotected and unnecessary personnel. Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs. Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up with inert absorbent material. Dispose of absorbent in accordance with local, state and federal regulations.

7. HANDLING AND STORAGE

Handling

Protect against electrostatic charges. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such contents to heat, flames, and other sources of ignition. Do not smoke.

Storage

Small pressurized containers of flammable product may be stored in areas suitable for ordinary combustibles with respect to construction, drainage, control of ignition sources, and ventilation except that they should not be stored in basements. Keep away from heat. Keep away from direct sunlight. Keep away from food, beverages, and feed. Do not freeze.

NFPA Storage Code

Store as Level 3 Aerosol (NFPA 30B)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Product code 97400

Product name Industrial Protective Coating High Solids
OSHA Blue

Chemical Name	OSHA PEL (TWA)	OSHA PEL (Ceiling)	ACGIH OEL (TWA)	ACGIH OEL (STEL)
Acetone	1000 ppm 2400 mg/m ³	-	500 ppm	750 ppm
Propane	1000 ppm 1800 mg/m ³	-	1000 ppm	-
N-Butane	-	-	1000 ppm	-
Barium Sulfate	0.5 mg/m ³ 0.5 mg/m ³ as Ba 15 mg/m ³ total dust 5 mg/m ³ respirable fraction	-	0.5 mg/m ³ 10 mg/m ³	-
Ethylene glycol monopropyl ether	-	-	-	-
Methylisobutyl ketone	100 ppm 410 mg/m ³	-	50 ppm	75 ppm
Titanium Dioxide	15 mg/m ³ total dust	-	10 mg/m ³	-
Methyl Propyl Ketone	200 ppm 700 mg/m ³	-	200 ppm	250 ppm
isobutyl acetate	150 ppm 700 mg/m ³	-	150 ppm	-
Xylene (mix)	100 ppm 435 mg/m ³	-	100 ppm	150 ppm

Ventilation and Environmental Controls

Adequate ventilation should be provided to keep exposure levels below current acceptable exposure limits.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product.

Personal protective equipment

Respiratory protection

None necessary under normal conditions. Use NIOSH approved respirator if TLV limit is exceeded. Protection provided by air purifying respirators is limited. Use a positive pressure supplied air respirator. If there is any potential for an uncontrolled release, where exposure levels are not known, or other circumstances where an air purifying respirator (P100) may not provide adequate protection.

Hand Protection

Protective gloves. For prolonged or repeated skin contact, use a chemically resistant glove such as nitrile or neoprene. Wash hands with soap and water after removing gloves. Dry hands thoroughly before re-applying gloves.

Eye protection

Tightly fitting safety goggles.

Skin and body protection

None necessary under normal conditions

9. PHYSICAL AND CHEMICAL PROPERTIES

Product code 97400

Product name Industrial Protective Coating High Solids
OSHA Blue

Form	Aerosol	Color	Blue
Odor	Solvent	Odor Threshold	5 ppm
pH	Not Applicable	Specific Gravity	0.77-0.90
Vapor pressure	40 psi	Vapor density	No data available
Evaporation Rate	No data available	VOC Content	46.4%; 464.5 gm/liter; 3.88 lb/gal
Water solubility	No data available	Partition Coefficient (n-octanol/water)	>1
		Boiling point/range °C	-44
Boiling point/range °F	-47	Melting point/range °C	Not Applicable
Melting point/range °F	Not Applicable	Flash point °C	-19
Flash point °F	-2		

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Conditions to avoid

Do not store in temperatures above 120 degrees F.

Incompatibility

No information available

Hazardous Decomposition Products

None known.

Polymerization

Hazardous polymerization does not occur

11. TOXICOLOGICAL INFORMATION

Component Information

Chemical Name	LD50 (oral, rat)	LD50 (dermal, rat/rabbit)	LC50 (inhalation, rat)
Acetone 67-64-1	1800 mg/kg	20000 mg/kg	76 mg/L
Propane 74-98-6	-	658 mg/kg	-
N-Butane 106-97-8	-	-	658 g/m ³
Barium Sulfate 7727-43-7	-	-	-
Ethylene glycol monopropyl ether 2807-30-9	3089 mg/kg	960 µL/kg	-
Methylisobutyl ketone 108-10-1	2080 mg/kg	16000 mg/kg	8.2 mg/L

Product code 97400

Product name Industrial Protective Coating High Solids
OSHA Blue

Titanium Dioxide 13463-67-7	10000 mg/kg	-	-
Methyl Propyl Ketone 107-87-9	1600 mg/kg	6500 mg/kg	-
Isobutyl acetate 110-19-0	13400 mg/kg	5000 mg/kg	-
Xylene (mix) 1330-20-7	4300 mg/kg	1700 mg/kg	5000 ppm

Synergistic Products

None known

Potential health effects

Sensitization

None known

Chronic toxicity

See Section 2.

Mutagenic effects

None known

Teratogenic effects

None known

Reproductive toxicity

None known

Target Organ Effects

None Known

Carcinogenic effects

See table below

Chemical Name	ACGIH OEL - Carcinogens	IARC	NTP - Known Carcinogens	NTP - Suspected Human Carcinogens	OSHA RTK Carcinogens
Acetone	Listed	Not Listed	Not Listed	Not Listed	Not Listed
Propane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
N-Butane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Barium Sulfate	Listed	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Methylisobutyl ketone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Titanium Dioxide	Listed	Not Listed	Not Listed	Not Listed	Not Listed
Methyl Propyl Ketone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Isobutyl acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Xylene (mix)	Listed	Not Listed	Not Listed	Not Listed	Not Listed

12. ECOLOGICAL INFORMATION

Acetone

Water Flea Data

water flea LC50=0.0039 mg/L (48 h)

water flea EC50=12700 mg/L (48 h)

Methylisobutyl ketone

Microtox Data

Photobacterium phosphoreum EC50=79.6 mg/L (5 min)

Product code 97400

Product name Industrial Protective Coating High Solids
OSHA Blue

Water Flea Data
water flea EC50=4280.0 mg/L (24 h)
Xylene (mix)

Microtox Data
Photobacterium phosphoreum EC50=0.0084 mg/L (24 h)

Water Flea Data
water flea EC50=3.82 mg/L (48 h)

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products
Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate. Please recycle empty container whenever possible.

14. TRANSPORT INFORMATION

DOT

UN1950 Aerosols, flammable (Propane/n-Butane/Acetone), Class 2.1
Exception: (Compressed Gas not more than 1.0L) Consumer Commodity ORM-D

TDG

UN1950 AEROSOLS(Propane/n-Butane/Acetone), Class 2.1

IMDG/IMO

UN1950 AEROSOLS (Propane/n-Butane/Acetone), Class 2.1

IATA

UN1950 Aerosols, flammable (Propane/n-Butane/Acetone), Class 2.1

MEX

UN1950 AEROSOLS (Propane/n-Butane/Acetone),2.1

15. REGULATORY INFORMATION

Chemical Name	US EPA SARA 313 Emission Reporting
Barium Sulfate	Listed
Ethylene glycol monopropyl ether	Listed
Methylisobutyl ketone	Listed
Xylene (mix)	Listed

Product code 97400

Product name Industrial Protective Coating High Solids
OSHA Blue

Chemical Name	New Jersey - RTK	Pennsylvania - RTK	California Prop. 65
Acetone	Listed	Listed	Not Listed
Propane	Listed	Listed	Not Listed
N-Butane	Not Listed	Listed	Not Listed
Barium Sulfate	Not Listed	Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Listed	Not Listed
Methylisobutyl ketone	Listed	Listed	Not Listed
Titanium Dioxide	Not Listed	Listed	Not Listed
Methyl Propyl Ketone	Not Listed	Listed	Not Listed
Isobutyl acetate	Listed	Listed	Not Listed
Xylene (mix)	Not Listed	Listed	Not Listed

Chemical Name	EINECS	DSL	NDSL	TSCA
Acetone	X	X	-	X
Propane	X	X	-	X
N-Butane	X	X	-	X
Barium Sulfate	X	X	-	X
Ethylene glycol monopropyl ether	X	X	-	X
Methylisobutyl ketone	X	X	-	X
Titanium Dioxide	X	X	-	X
Methyl Propyl Ketone	X	X	-	X
Isobutyl acetate	X	X	-	X
Xylene (mix)	X	X	-	X

CPRC

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by the Controlled Product Regulations

16. OTHER INFORMATION

NFPA		HMIS	
Health	1	Health	1
Flammability	4	Flammability	4
Reactivity	3	Physical Hazard	3

Prepared By

Michael Katz, Regulatory Affairs Specialist

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.



Material Safety Data Sheet

Product code 53387

Product name HSP New Equipment Yellow

Revision Date 30-Oct-2007

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product code 53387
Product name HSP New Equipment Yellow
Recommended Use Coating
Supplier Lawson Products, Inc.
1666 East Touhy Avenue
Des Plaines, IL 60018
(847)-827-9666

Emergency telephone number (888) 426-4851

2. HAZARDS IDENTIFICATION

Emergency Overview
Extremely flammable. Harmful by inhalation.

Color Yellow **Odor** Solvent **Form** Aerosol

Aggravated Medical Conditions None Known
Principal Routes of Exposure Inhalation. Eyes. Ingestion.

Potential health effects

Eyes Contact with eyes may cause irritation. Swelling.
Skin Exposure to vapors may cause the following effects. Skin Irritation.
Inhalation Harmful by inhalation. Exposure to vapors may cause the following effects. Irritation of the nose or throat. Central nervous system effects. Dizziness. Drowsiness . Headaches. Fatigue. Nausea. Lung damage. Changes in heart rate.
Ingestion Harmful or fatal if swallowed.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No	Weight %
Methyl Propyl Ketone	107-87-9	1-5
Acetone	67-64-1	10-30
Propane	74-98-6	10-30
N-Butane	106-97-8	7-13
Barium Sulfate	7727-43-7	7-13
Ethylene glycol monopropyl ether	2807-30-9	3-7
Methylisobutyl ketone	108-10-1	3-7
Xylene (mix)	1330-20-7	1-5
PM Acetate	108-65-6	1-5
Isobutyl acetate	110-19-0	1-5
Titanium dioxide	13463-67-7	0.1-1

4. FIRST AID MEASURES

Eye contact Keep eye wide open while rinsing. If symptoms persist, call a physician.
Skin contact Remove and wash contaminated clothing before re-use. Wash area thoroughly with soap and water.
Ingestion Contact physician or poison control center immediately.
Inhalation Remove to fresh air. Consult a physician.

5. FIRE FIGHTING MEASURES

Flash point °C -19
Flash point °F -2
Method No information available
Autoignition temperature °C No data available
Autoignition temperature °F No data available
Flammability Limits (% in Air)
Upper 10.9
Lower 1.7

Suitable extinguishing media

Carbon dioxide (CO2). Sand. Dry powder. Water spray. Alcohol-resistant foam .

Special protective equipment for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Fire and Explosion Hazards

Keep product and empty container away from heat and sources of ignition. Contents under pressure. Aerosol containers may vent, rupture or burst when heated to temperatures above 120°F. Vapors may form explosive mixture in air between upper and lower explosive limits which can be ignited by many sources, such as pilot lights, open flames, electrical motors and switches. Empty containers contain residue and/or vapors. Do not weld, cut, pressurize, braze, solder, drill, grind, or expose such containers to heat, sparks, flame, static electricity, or other sources of ignition. They may explode and cause injury or death.

Sensitivity to shock
No information available.

Sensitivity to static discharge
Yes. Take precautionary measures against static discharges

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Remove all sources of ignition. Ensure adequate ventilation.

Methods for cleaning up

Prevent product from entering drains. Personnel should wear appropriate protective equipment. Follow all precautions for handling. Please refer to appropriate sections of MSDS for additional information. Do not allow product to reach sewage system, soil, surface or ground water, or any water course. Notify proper authorities if entry occurs. Do not flush with water or aqueous cleansing agents. Use diluted caustic solution. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

7. HANDLING AND STORAGE

Handling

Control airborne concentration below exposure level. Handle carefully to avoid damaging. Turn off other sources of ignition prior to use and until all vapors have dissipated. Do not spray on a naked flame or any other incandescent material. Do not smoke while using. Protect against electrostatic charges. Thoroughly wash hands and exposed skin after handling. Wash hands with soap and water before eating, drinking, smoking, or using toilet facilities.

Storage

Small pressurized containers of flammable product may be stored in areas suitable for ordinary combustibles with respect to construction, drainage, control of ignition sources, and ventilation except that they should not be stored in basements. Keep away from direct sunlight. Keep away from heat. Do not freeze.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limits

Chemical Name	OSHA PEL (TWA)	OSHA PEL (Ceiling)	ACGIH OEL (TWA)	ACGIH OEL (STEL)
Acetone	1000 ppm 2400 mg/m ³	-	500 ppm	750 ppm
Propane	1000 ppm 1800 mg/m ³	-	1000 ppm	-
N-Butane	-	-	1000 ppm	-
Barium Sulfate	0.5 mg/m ³ 0.5 mg/m ³ as Ba 15 mg/m ³ total dust 5 mg/m ³ respirable fraction	-	0.5 mg/m ³ 10 mg/m ³	-
Ethylene glycol monopropyl ether	-	-	-	-
Methylisobutyl ketone	100 ppm 410 mg/m ³	-	50 ppm	75 ppm
Methyl Propyl Ketone	200 ppm 700 mg/m ³	-	200 ppm	250 ppm
Xylene (mix)	100 ppm 435 mg/m ³	-	100 ppm	150 ppm
PM Acetate	-	-	-	-
Isobutyl acetate	150 ppm 700 mg/m ³	-	150 ppm	-
Titanium dioxide	15 mg/m ³ total dust	-	10 mg/m ³	-

Ventilation and Environmental Controls

Ensure adequate ventilation, especially in confined areas.

Hygiene measures

Keep away from food, drink and animal feeding stuffs. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

Other precautions

Avoid contact with eyes

Personal protective equipment

Respiratory protection

None required if adequate ventilation is provided. Recommended for confined environments. If the exposure limits are exceeded, a NIOSH/MSHA approved respirator is recommended. Seek professional advice prior to respirator selection and use.

Hand Protection

Gloves are recommended to prevent prolonged or repeated contact. Consult glove manufacturer to determine the proper type for a specific operation.

Eye protection

Tightly fitting safety goggles.

Skin and body protection

None necessary under normal conditions

Other Protective Equipment

No information available.

Environmental exposure controls

Do not allow material to contaminate ground water system.

9. PHYSICAL AND CHEMICAL PROPERTIES

Form	Aerosol	Color	Yellow
Odor	Solvent	Odor Threshold	No information available
pH	No data available	Specific Gravity	0.77-0.85
Vapor pressure	40 PSI	Vapor density	No data available
Evaporation Rate	No data available	Density	0.85916 g/cm ³ @ 68°F
VOC Content	501.5 g/l; 4.26 lb/gl	Water solubility	No data available
Partition Coefficient (n-octanol/water)	No data available		
Boiling point/range °C	-44	Boiling point/range °F	-47
Melting point/range °C	No data available	Melting point/range °F	No data available
Flash point °C	-19	Flash point °F	-2

10. STABILITY AND REACTIVITY**Stability**

Stable under normal conditions.

Conditions to avoid

Do not store in temperatures above 120 degrees F.

Incompatibility

None known.

Hazardous Decomposition Products

None known.

Polymerization

Hazardous polymerization does not occur

11. TOXICOLOGICAL INFORMATION**Component Information**

Chemical Name	LD50 (oral, rat)	LD50 (dermal, rat/rabbit)	LC50 (inhalation, rat)
Acetone 67-64-1	1800 mg/kg	20000 mg/kg	76 mg/L
Propane 74-98-6	-	658 mg/kg	-
n-Butane 106-97-8	-	-	658 g/m ³
Barium Sulfate 7727-43-7	-	-	-

Chemical Name	LD50 (oral, rat)	LD50 (dermal, rat/rabbit)	LC50 (inhalation, rat)
Ethylene glycol monopropyl ether 2807-30-9	3089 mg/kg	960 µL/kg	-
Methylisobutyl ketone 108-10-1	2080 mg/kg	16000 mg/kg	8.2 mg/L
Methyl Propyl Ketone 107-87-9	1600 mg/kg	6500 mg/kg	-
Xylene (mix) 1330-20-7	4300 mg/kg	1700 mg/kg	5000 ppm
PM Acetate 108-65-6	8532 mg/kg	5000 mg/kg	-
Isobutyl acetate 110-19-0	13400 mg/kg	5000 mg/kg	-
Titanium dioxide 13463-67-7	10000 mg/kg	-	-

Synergistic Products

None known

Potential health effects**Sensitization**

None known

Mutagenic effects

None known

Reproductive toxicity

None known

Carcinogenic effects

See table below

Chemical Name	ACGIH OEL - Carcinogens	IARC	NTP - Known Carcinogens	NTP - Suspected Human Carcinogens	OSHA RTK Carcinogens
Acetone	Listed	Not Listed	Not Listed	Not Listed	Not Listed
Propane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
n-Butane	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Barium Sulfate	Listed	Not Listed	Not Listed	Not Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Methylisobutyl ketone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Methyl Propyl Ketone	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Xylene (mix)	Listed	Not Listed	Not Listed	Not Listed	Not Listed
PM Acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Isobutyl acetate	Not Listed	Not Listed	Not Listed	Not Listed	Not Listed
Titanium dioxide	Listed	Not Listed	Not Listed	Not Listed	Not Listed

Chronic toxicity

Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

Teratogenic effects

None known

Target Organ Effects

Long term exposure to vapor may cause liver damage. Long term exposure to vapor may cause kidney damage. May cause damage to blood, Heart.

Product code 53387

Product name HSP New Equipment Yellow

Specific Hazards Misuse by deliberately concentrating vapors and inhaling contents can be harmful or fatal.

12. ECOLOGICAL INFORMATION

Acetone

Water Flea Data

water flea LC50=0.0039 mg/L (48 h)

water flea EC50=12700 mg/L (48 h)

Methylisobutyl ketone

Microtox Data

Photobacterium phosphoreum EC50=79.6 mg/L (5 min)

Water Flea Data

water flea EC50=4280.0 mg/L (24 h)

Xylene (mix)

Microtox Data

Photobacterium phosphoreum EC50=0.0084 mg/L (24 h)

Water Flea Data

water flea EC50=3.82 mg/L (48 h)

Aquatic toxicity

Harmful to aquatic organisms

13. DISPOSAL CONSIDERATIONS

Disposal Information

Dispose in accordance with federal, state, and local regulations. Do not puncture or incinerate. Dispose cans in non-incinerated trash.

Waste from residues / unused products

Dispose of in accordance with local regulations.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.

14. TRANSPORT INFORMATION

DOT

UN1950 Aerosols, flammable (Propane/n-Butane), Class 2.1

Exception: (Compressed Gas not more than 1.0L) Consumer Commodity ORM-D

TDG

UN1950 AEROSOLS (Propane/n-Butane), Class 2.1 (Consumer Commodity, ORM-D)

IMDG/IMO

UN1950 AEROSOLS (Propane/n-Butane), Class 2.1

IATA

UN1950 Aerosols, flammable (Propane/n-Butane), Class 2.1

Product code 53387

Product name HSP New Equipment Yellow

14. TRANSPORT INFORMATION

MEX

UN1950 AEROSOLS (Propano/n-Butano), 2.1

15. REGULATORY INFORMATION

Chemical Name	US EPA SARA 313 Emission Reporting
Barium Sulfate	Listed
Ethylene glycol monopropyl ether	Listed
Methylisobutyl ketone	Listed
Xylene (mix)	Listed

Chemical Name	New Jersey - RTK	Pennsylvania - RTK	California Prop. 65
Acetone	Not Listed	Listed	
Propane	Not Listed	Listed	Not Listed
N-Butane	Not Listed	Listed	Not Listed
Barium Sulfate	Not Listed	Listed	Not Listed
Ethylene glycol monopropyl ether	Not Listed	Listed	Not Listed
Methylisobutyl ketone	Listed	Listed	Not Listed
Methyl Propyl Ketone	Not Listed	Listed	Not Listed
Xylene (mix)	Not Listed	Listed	Not Listed
PM Acetate	Not Listed	Not Listed	Not Listed
Isobutyl acetate	Listed	Listed	Not Listed
Titanium dioxide	Not Listed	Listed	Not Listed

Chemical Name	EINECS	DSL	NDSL	TSCA
Acetone	X	X	-	X
Propane	X	X	-	X
N-Butane	X	X	-	X
	X			
Barium Sulfate	X	X	-	X
	X			
Ethylene glycol monopropyl ether	X	X	-	X
Methylisobutyl ketone	X	X	-	X
Methyl Propyl Ketone	X	X	-	X
Xylene (mix)	X	X	-	X
PM Acetate	X	X	-	X
Isobutyl acetate	X	X	-	X
Titanium dioxide	X	X	-	X
	X			
	X			

CPRC

This product has been classified in accordance with the hazard criteria of the Controlled Product Regulations and the MSDS contains all of the information required by the Controlled Product Regulations

Product code 53387

Product name HSP New Equipment Yellow

16. OTHER INFORMATION

NFPA		HMIS	
Health	1	Health	1
Flammability	4	Flammability	4
Reactivity	3	Physical Hazard	3

Prepared By Michael Katz, Regulatory Affairs Specialist

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.