

010312587-00  
Rep Order#:

PO#: 45984

PAGE 1

MSDS

VALMONT INDUSTRIES  
58027 CHARLOTTE AVENUE  
ELKHART IN 46517

07-030  
Touch Up Paint

Rep Order#:

PO#: 45984

FOR COATINGS, RESINS, AND RELATED MATERIALS  
 (APPROVED BY THE U.S. DEPARTMENT OF LABOR AS  
 'ESSENTIALLY SIMILAR' TO FORM OSHA-20)  
 (MEETS REQUIREMENTS OF CFR 29 PART 1910.1200,  
 OSHA'S HAZARD COMMUNICATION STANDARD)

NPCA 1-84

 -----  
 SECTION 1 - MANUFACTURER AND PRODUCT INFORMATION  
 -----

## CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID . . . . . : 1075-CLEAR 1G  
 PRODUCT CLASS . . . . . : ACRYLIC  
 TRADE NAME . . . . . : ENDURA-SHIELD II CLEAR BA  
 FORMULA VERSION NUMBER . . . . . : 13  
 MSDS PREPARATION DATE . . . . . : 04/29/2008

## MANUFACTURER IDENTIFICATION:

NAME . . . . . : TNEMEC COMPANY, INC.  
 ADDRESS . . . . . : 123 WEST 23RD AVENUE  
 NORTH KANSAS CITY, MO. 64116-3064  
 TELEPHONE . . . . . : 816-474-3400  
 24 HOUR EMERGENCY NUMBER . . . . . : 800-535-5053 (INFOTRAC)

 -----  
 SECTION 2 - HAZARDOUS INGREDIENTS  
 -----

1

CAS# 14808-60-7  
 CRYSTALLINE SILICA (QUARTZ)  
 PCT BY WT: 48.9940  
 EXPOSURE LIMIT:  
 ACGIH TLV/TWA: 0000.025 MG/M3  
 OSHA PEL/TWA: 0000.050 MG/M3  
 EXPOSURE LIMIT:  
 HAPS: N

2

CAS# 14808-60-7  
 CRYSTALLINE SILICA (QUARTZ)  
 PCT BY WT: .2070  
 EXPOSURE LIMIT:  
 ACGIH TLV/TWA: 0000.025 MG/M3  
 OSHA PEL/TWA: 0000.050 MG/M3  
 EXPOSURE LIMIT:  
 HAPS: N

3 ACETIC ACID BUTYL ESTER

CAS# 123-86-4  
 N-BUTYL ACETATE  
 PCT BY WT: 8.6330 VAPOR PRESSURE: 10.000 MMHG @ 68F  
 EXPOSURE LIMIT:  
 ACGIH TLV/TWA: 0150.000 PPM  
 ACGIH TLV/STEL: 0200.000 PPM  
 OSHA PEL/TWA: 0150.000 PPM  
 OSHA STEL: 0200.000 PPM  
 EXPOSURE LIMIT:  
 HAPS: N

4 2-HEPTANONE

CAS# 110-43-0  
 METHYL N-AMYL KETONE  
 PCT BY WT: 5.8060 VAPOR PRESSURE: 2.100 MMHG @ 68F  
 EXPOSURE LIMIT:  
 ACGIH TLV/TWA: 0050.000 PPM  
 OSHA PEL/TWA: 0100.000 PPM  
 EXPOSURE LIMIT:  
 HAPS: N

This product contains one or more reported carcinogens or suspected  
 carcinogens which are noted NTP, IARC, or OSHA-Z in the other limits  
 recommended column.  
 This product contains pigment dusts which may be released when subjected to  
 abrasive blasting, sanding, or grinding.

 -----  
 SECTION 3 - HEALTH HAZARD INFORMATION  
 -----

## EMERGENCY OVERVIEW:

## POTENTIAL HEALTH EFFECTS:

EYE:  
 Redness, tearing, blurred vision.

Rep Order#:

PO#: 45984

Severe irritation.

## SKIN:

Moderate irritation, drying of skin, defatting and possible dermatitis.

## INHALATION - OVEREXPOSURE TO SOLVENT VAPORS OR SPRAY MIST:

Nasal and respiratory irritation, anesthetic effects, dizziness, possible unconsciousness and asphyxiation, stupor, weakness, fatigue, nausea, and headache.

## INHALATION - OVEREXPOSURE TO FREE PIGMENT DUST:

Coughing, wheezing, shortness of breath, restricted nasal passages, lung injury.

## INGESTION:

Gastrointestinal irritation, nausea, vomiting, diarrhea, death, aspiration into the lungs which can be fatal.

## CHRONIC EFFECTS:

Prolonged inhalation of dusts containing crystalline silica may result in the development of a lung disease known as silicosis.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal.

This product contains crystalline silica, which is considered a cancer hazard by inhalation of respirable dust. The International Agency for Research on Cancer (IARC) concluded that respirable crystalline silica inhaled in the form of quartz or cristobalite from occupational sources is carcinogenic to humans (Group 1B).

## TARGET ORGANS:

Can cause respiratory tract irritation.

Can cause skin irritation.

Can cause lung damage.

Can cause eye irritation.

Can cause gastrointestinal tract irritation.

Can cause nervous system effects.

Can cause cancer. Risk of cancer depends on duration and level of exposure

Can cause liver damage.

## OTHER:

This product when mixed with other components acquires the hazards of all components.

## PRIMARY ROUTES OF ENTRY:

Dermal and Inhalation.

## PROPOSITION 65:

This product contains a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

-----  
SECTION 4 - FIRST AID MEASURES  
-----

## EYE CONTACT:

Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician.

## SKIN CONTACT:

Wash affected area with soap and water. Remove contaminated clothing; Dispose of or launder accordingly. Consult a physician if skin irritation persists.

## INHALATION:

Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician.

## INGESTION:

Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center IMMEDIATELY. Treat symptomatically.

## NOTE TO PHYSICIAN:

-----  
SECTION 5 - FIRE AND EXPLOSION HAZARD DATA  
-----

## FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification . . . . .	:	
Flashpoint . . . . .	:	98.0 °F
Explosion Level . . . . .	:	Low - 1.1
		High - -N/A
Flammability Limits . . . . .	:	Lower - -N/A
		Higher - -N/A

## EXTINGUISHING MEDIA:

Foam, carbon dioxide, and dry chemical.

## FIRE-FIGHTING PROCEDURES AND EQUIPMENTS:

Keep away from heat, open flames, sparks, and areas where static charge may be generated. Do not apply to hot surfaces due to

Rep Order#:

PO#: 45984

TNE MEC COMPANY, INC.  
MATERIAL SAFETY DATA SHEET  
AE

1075-CLEAR 1G

ENDURA-SHIELD II CLEAR BA

possible fire and explosion risk. For closed containers, pressure build-up and possible explosion might occur due to extreme heat exposure. Solvent vapors are heavier than air and may travel considerable distance to a source of ignition and flash back. Water may be used to cool unruptured containers. Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode to prevent inhalation of hazardous decomposition products. Use appropriate extinguishing media to control fire. Water may cause violent frothing if sprayed directly into containers of burning liquid.

## SECTION 6 - SPILL OR LEAK PROCEDURES

## CLEAN-UP:

Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal. Remove containers to a safe place and cover loosely until carbon dioxide has finished evolving.

## SECTION 7 - SPECIAL PRECAUTIONS

## HANDLING AND STORAGE:

Store in dry area. Keep closures tight and upright to prevent leakage. Do not store in high temperature areas or near fire or open flame. Refer to product data sheet for recommended storage temperatures.

## SPECIAL COMMENTS:

Prevent prolonged breathing of airborne contaminants such as vapor, spray mists, or dusts. Prevent contact with skin and eyes. Do not take internally. Keep out of reach of children. Do not reuse or alter containers without proper industrial cleaning. Do not weld or flame cut empty, uncleaned containers due to potential fire and explosion hazard. Consult product data sheet for proper application instructions.

## SECTION 8 - SAFE HANDLING AND USE INFORMATION

## HYGIENIC PRACTICES:

Wash hands and other contaminated skin areas with warm soap and water before eating.

## EYE PROTECTION:

Use chemical resistant splash type goggles.

## RESPIRATORY PROTECTION:

Respiratory protective devices must be used when engineering and administration controls are not adequate to maintain Threshold Limit Values (TLV) and Permissible Exposure Limits (PEL) of airborne contaminants below the listed values for those hazardous ingredients identified in Section II of this MSDS. Observe OSHA regulations for respirator use (CFR 29, 1910.134) whenever a respirator is used. Particulate, chemical cartridge, air purifying half-mask respirators can be used within certain limitations; consult the respirator manufacturer for specific uses and limitations. Where airborne contaminant concentrations are unknown, the use of a NIOSH/MSHA approved fresh-air supplied respirator is mandatory.

## OTHER PROTECTION:

Use Chemical resistant gloves.

Use chemical resistant coveralls or apron to protect against skin and clothing contamination.

Use protective cream where skin contact is likely.

## VENTILATION:

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Rep Order#: PO#: 45984  
 Heavier than air solvent vapors should be removed from lower levels of work area due to potential explosion hazard and all ignition sources (non-explosion proof equipment) should be eliminated if flammable mixtures will be encountered.

-----  
 SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES  
 -----

Vapor Pressure . . . . .	:	10.00	
Vapor Density . . . . .	:	-N/A	
Boiling Range . . . . .	:	Lower - 244.0	°F
	:	Higher - 309.0	°F
Formula Weight per Volume . . . . .	:	12.1130	LB/GL
VOC IN LBS PER GALLON . . . . .	:	1.930	
Evaporation Rate . . . . .	:	17.400	(Ether = 1)
% Volatile by Weight . . . . .	:	15.935	
% Volatile by Volume . . . . .	:	27.060	

-----  
 SECTION 10 - STABILITY AND REACTIVITY  
 -----

INCOMPATIBILITIES:  
 Strong oxidizing agents.  
 Caustics.  
 DECOMPOSITION:  
 Carbon monoxide, carbon dioxide, hydrocarbon fragments  
 CONDITIONS TO AVOID:  
 Heat, sparks, open flames.  
 POLYMERIZATION:  
 Will not occur.  
 STABILITY:  
 Stable.

-----  
 SECTION 11 - TOXICOLOGICAL INFORMATION  
 -----

OTHER:  
 Consult various toxicology references such as NIOSH's "Registry of Toxic Effects of Chemical Substances" or Sax's "Dangerous Properties of Industrial Chemicals" for specific toxicity information regarding hazardous ingredients.

-----  
 SECTION 12 - ECOLOGICAL INFORMATION  
 -----

ECOTOXICOLOGICAL INFORMATION:

-----  
 SECTION 13 - DISPOSAL CONSIDERATIONS  
 -----

WASTE DISPOSAL:  
 Dispose of in accordance with Federal, state, and local regulations regarding pollution.

-----  
 SECTION 14 - TRANSPORT INFORMATION  
 -----

DOT HAZARD CLASS . . . . .  
 DOT LINE NUMBER: UN1263, PAINT, 3, PGIII, ERG 128  
 TRANSPORTATION ASSISTANCE:  
 The above information is based on USDOT regulations for ground shipments in the container size specified on the MSDS. For further information please contact Tnemec's Traffic Dept. at (816)474-3400.

-----  
 SECTION 15 - REGULATORY INFORMATION  
 -----

EPA TSCA:  
 All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory

FEDERAL REGULATIONS:  
 There are no SARA reportable materials in this product.  
 This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.  
 STATE REGULATIONS:

1075-CLEAR 1G

TNEMEC COMPANY, INC.  
MATERIAL SAFETY DATA SHEET  
AE

ENDURA-SHIELD II CLEAR BA

SECTION 16 - OTHER INFORMATION

Prepared by . . . . . : Kevin Settles  
Date of issue . . . . . : 04/29/2008  
Last Revision Date . . . . . : 01/14/2008

MSDS Prepared for . . . . . : RAUHORN ELECTRIC, INC.  
ATTN: CLIFF (586)992-0400  
17171 23 MILE ROAD

MACOMB MI 48042

MSDS Last Prepared . . . . . : 04/29/2008

HMIS Information: Health- 2\* Flammability- 3  
Reactivity- 1

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.  
To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

010312587-00  
Rep Order#:

PO#: 45984

PAGE 1

VALMONT INDUSTRIES  
58027 CHARLOTTE AVENUE  
ELKHART IN 46517

Rep Order#:

PO#: 45984

FOR COATINGS, RESINS, AND RELATED MATERIALS  
 (APPROVED BY THE U.S. DEPARTMENT OF LABOR AS  
 'ESSENTIALLY SIMILAR' TO FORM OSHA-20)  
 (MEETS REQUIREMENTS OF CFR 29 PART 1910.1200,  
 OSHA'S HAZARD COMMUNICATION STANDARD)

NPCA 1-84

 -----  
 SECTION 1 - MANUFACTURER AND PRODUCT INFORMATION  
 -----

## CHEMICAL PRODUCT IDENTIFICATION:

PRODUCT ID . . . . . : 1074-1075B PT  
 PRODUCT CLASS . . . . . : POLYISOCYANATE  
 TRADE NAME . . . . . : 1074/1075 CONVERTER  
 FORMULA VERSION NUMBER . . . . . : 10  
 MSDS PREPARATION DATE . . . . . : 04/29/2008

## MANUFACTURER IDENTIFICATION:

NAME . . . . . : TNEMEC COMPANY, INC.  
 ADDRESS . . . . . : 123 WEST 23RD AVENUE  
 NORTH KANSAS CITY, MO. 64116-3064  
 TELEPHONE . . . . . : 816-474-3400  
 24 HOUR EMERGENCY NUMBER . . . . . : 800-535-5053 (INFOTRAC)

 -----  
 SECTION 2 - HAZARDOUS INGREDIENTS  
 -----

1  
 CAS# 28182-81-2  
 HEXAMETHYLENE DIISOCYANATE (HDI) POLYMER  
 PCT BY WT: 81-90  
 EXPOSURE LIMIT:  
 ACGIH TLV/TWA: 0000.500 MG/M3 MFG REC  
 ACGIH TLV/STEL: 0001.000 MG/M3 MFG REC  
 EXPOSURE LIMIT:  
 HAPS: N

2 ACETIC ACID BUTYL ESTER  
 CAS# 123-86-4  
 N-BUTYL ACETATE  
 PCT BY WT: 5.0000 VAPOR PRESSURE: 10.000 MMHG @ 68F  
 EXPOSURE LIMIT:  
 ACGIH TLV/TWA: 0150.000 PPM  
 ACGIH TLV/STEL: 0200.000 PPM  
 OSHA PEL/TWA: 0150.000 PPM  
 OSHA STEL: 0200.000 PPM  
 EXPOSURE LIMIT:  
 HAPS: N

3  
 CAS# 64742-95-6  
 PETROLEUM SOLVENT (NAPTHA)  
 PCT BY WT: 5.0000  
 EXPOSURE LIMIT:  
 ACGIH TLV/TWA: 0300.000 PPM  
 OSHA PEL/TWA: 0400.000 PPM  
 EXPOSURE LIMIT:  
 HAPS: N

This product contains no reported carcinogens or suspected carcinogens.  
 Contains isocyanate monomer. If subject to spray application,  
 engineering and administrative controls must be instituted to  
 maintain an exposure level below .005ppm. If these controls are  
 not adequate, the use of an air-supplied respirator is mandatory.

 -----  
 SECTION 3 - HEALTH HAZARD INFORMATION  
 -----

## EMERGENCY OVERVIEW:

## POTENTIAL HEALTH EFFECTS:

## EYE:

Redness, tearing, blurred vision.  
 Severe irritation.

## SKIN:

Moderate irritation, drying of skin, defatting and possible  
 dermatitis.

Allergic skin responses.

INHALATION - OVEREXPOSURE TO SOLVENT VAPORS OR SPRAY MIST:  
 Nasal and respiratory irritation, anesthetic effects, dizziness,  
 possible unconsciousness and asphyxiation, stupor, weakness,  
 fatigue, nausea, and headache.

INHALATION - OVEREXPOSURE TO FREE PIGMENT DUST:



Rep Order#:

PO#: 45984

## INGESTION:

Gastrointestinal irritation, nausea, vomiting, diarrhea, death, aspiration into the lungs which can be fatal.

## CHRONIC EFFECTS:

Prolonged contact or repeated exposure to isocyanate concentrations greater than the recommended TLV may result in permanent respiratory and skin sensitization. Once diagnosed as being sensitized to isocyanates, no further exposure can be permitted.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the vapors may be harmful or fatal.

## TARGET ORGANS:

Can cause eye damage.  
Can cause skin irritation.  
Can cause respiratory tract irritation.  
Can cause lung damage.  
Can cause nervous system effects.  
Can be corrosive to gastrointestinal tract.  
Can cause skin sensitization.  
Can cause respiratory tract sensitization.

## OTHER:

This product when mixed with other components acquires the hazards of all components.

## PRIMARY ROUTES OF ENTRY:

Dermal and Inhalation.

## PROPOSITION 65:

Pigments and/or other raw materials present in this product contain trace amounts of a chemical or chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

-----  
SECTION 4 - FIRST AID MEASURES  
-----

## EYE CONTACT:

Flush immediately with large amounts of clean water under low pressure for at least 15 minutes. Consult a physician.

## SKIN CONTACT:

Wash affected area with soap and water. Remove contaminated clothing. Dispose of or launder accordingly. Consult a physician if skin irritation persists.

## INHALATION:

Remove affected individual to fresh air. Treat symptomatically. If breathing is difficult, administer oxygen. If breathing has stopped give artificial respiration. Consult a physician.

## INGESTION:

Drink 1 or 2 glasses of water to dilute. Do not induce vomiting. Consult a physician or poison control center IMMEDIATELY. Treat symptomatically.

## NOTE TO PHYSICIAN:

Exposure to isocyanate products may aggravate persons with asthmatic type conditions, chronic bronchitis, other chronic respiratory diseases, skin eczema, or skin sensitization.

-----  
SECTION 5 - FIRE AND EXPLOSION HAZARD DATA  
-----

## FIRE AND EXPLOSIVE PROPERTIES OF THE CHEMICAL:

Flammability Classification . . . . .	:	
Flashpoint . . . . .	:	135.0 °F
Explosion Level . . . . .	:	Low - 1.7
		High - -N/A
Flammability Limits . . . . .	:	Lower - -N/A
		Higher - -N/A

## EXTINGUISHING MEDIA:

Foam, carbon dioxide, and dry chemical.

## FIRE-FIGHTING PROCEDURES AND EQUIPMENTS:

Keep away from heat, open flames, sparks, and areas where static charge may be generated. Do not apply to hot surfaces due to possible fire and explosion risk. For closed containers, pressure build-up and possible explosion might occur due to extreme heat exposure. Solvent vapors are heavier than air and may travel considerable distance to a source of ignition and flash back. Small traces of HCN may be evolved under fire conditions. Water may be used to cool unruptured containers. Wear self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode to prevent inhalation of hazardous decomposition products. Use appropriate extinguishing media to control fire. Water may cause violent frothing if sprayed

Rep Order#:

PO#: 45984

1074-1075B PT

TNE MEC COMPANY, INC.  
MATERIAL SAFETY DATA SHEET  
AC

1074/1075 CONVERTER

directly into containers of burning liquid.

#### SECTION 6 - SPILL OR LEAK PROCEDURES

##### CLEAN-UP:

Remove all sources of ignition. Spills may be collected with inert, absorbent material for proper disposal. Use non-sparking tools, protective gloves, goggles and clothing, adequate ventilation, avoid the breathing of vapors and use respiratory protective devices. Transfer absorbent material to suitable containers for proper disposal. Remove containers to a safe place and cover loosely until carbon dioxide has finished evolving.

#### SECTION 7 - SPECIAL PRECAUTIONS

##### HANDLING AND STORAGE:

Store in dry area. Keep closures tight and upright to prevent leakage. Do not store in high temperature areas or near fire or open flame. Refer to product data sheet for recommended storage temperatures.

##### SPECIAL COMMENTS:

Prevent prolonged breathing of airborne contaminants such as vapor, spray mists, or dusts. Prevent contact with skin and eyes. Do not take internally. Keep out of reach of children. Do not reuse or alter containers without proper industrial cleaning. Do not weld or flame cut empty, uncleaned containers due to potential fire and explosion hazard. Consult product data sheet for proper application instructions.

#### SECTION 8 - SAFE HANDLING AND USE INFORMATION

##### HYGIENIC PRACTICES:

Wash hands and other contaminated skin areas with warm soap and water before eating.

##### EYE PROTECTION:

Use chemical resistant splash type goggles.

##### RESPIRATORY PROTECTION:

Respiratory protective devices must be used when engineering and administration controls are not adequate to maintain Threshold Limit Values (TLV) and Permissible Exposure Limits (PEL) of airborne contaminants below the listed values for those hazardous ingredients identified in Section II of this MSDS. Observe OSHA regulations for respirator use (CFR 29, 1910.134) whenever a respirator is used. Particulate, chemical cartridge, air purifying half-mask respirators can be used within certain limitations; consult the respirator manufacturer for specific uses and limitations. Where airborne contaminant concentrations are unknown, the use of a NIOSH/MSHA approved fresh-air supplied respirator is mandatory.

##### OTHER PROTECTION:

Use Chemical resistant gloves.

Use chemical resistant coveralls or apron to protect against skin and clothing contamination.

Use protective cream where skin contact is likely.

##### VENTILATION:

Sufficient ventilation, in volume and pattern, should be provided through both local and general exhaust to keep the air contaminant concentration below current applicable OSHA Permissible Exposure Limits (PEL) and ACGIH's Threshold Limit Values (TLV). Appropriate ventilation should be employed to remove hazardous decomposition products formed during welding or flame cutting operations of surfaces coated with this product.

Heavier than air solvent vapors should be removed from lower levels of work area due to potential explosion hazard and all ignition sources (non-explosion proof equipment) should be eliminated if flammable mixtures will be encountered.

#### SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Rep Order#:	PO#:	45984
Vapor Pressure . . . . .	10.00	
Vapor Density . . . . .	-N/A	
Boiling Range . . . . .	Lower -	244.0 °F
	Higher -	262.0 °F
Formula Weight per Volume . . . . .	9.3495	LB/GL
VOC IN LBS PER GALLON . . . . .	.935	
Evaporation Rate . . . . .	7.800	(Ether = 1)
% Volatile by Weight . . . . .	9.999	
% Volatile by Volume . . . . .	13.900	

SECTION 10 - STABILITY AND REACTIVITY

INCOMPATIBILITIES:

Strong oxidizing agents.  
Water, alcohols, amines, strong bases, metal components, surface active materials.

Caustics.

DECOMPOSITION:

Carbon monoxide, carbon dioxide, hydrocarbon fragments  
Nitrogen monoxide, nitrogen dioxide  
Trace amounts of HCN.

CONDITIONS TO AVOID:

Amine compounds under uncontrolled conditions.  
Heat, sparks, open flames.

POLYMERIZATION:

Will not occur.

STABILITY:

Stable.

SECTION 11 - TOXICOLOGICAL INFORMATION

OTHER:

Consult various toxicology references such as NIOSH's "Registry of Toxic Effects of Chemical Substances" or Sax's "Dangerous Properties of Industrial Chemicals" for specific toxicity information regarding hazardous ingredients.

SECTION 12 - ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION:

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL:

Dispose of in accordance with Federal, state, and local regulations regarding pollution.

SECTION 14 - TRANSPORT INFORMATION

DOT HAZARD CLASS . . . . . :

DOT LINE NUMBER: PAINT IN OIL

TRANSPORTATION ASSISTANCE:

The above information is based on USDOT regulations for ground shipments in the container size specified on the MSDS. For further information please contact Tnemec's Traffic Dept. at (816)474-3400.

SECTION 15 - REGULATORY INFORMATION

EPA TSCA:

All components of this product are listed or are excluded from listing on the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

FEDERAL REGULATIONS:

There are no SARA reportable materials in this product.

This product contains NONE of the substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

STATE REGULATIONS:

SECTION 16 - OTHER INFORMATION

Rep Order#:

PO#: 45984

TNEMEC COMPANY, INC.  
MATERIAL SAFETY DATA SHEET  
AC

1074-1075B PT

1074/1075 CONVERTER

Prepared by . . . . . : Kevin Settles  
Date of issue . . . . . : 04/29/2008  
Last Revision Date . . . . . : 09/18/2007  
MSDS Prepared for . . . . . : RAUHORN ELECTRIC, INC.  
ATTN: CLIFF (586)992-0400  
17171 23 MILE ROAD

MACOMB MI 48042

MSDS Last Prepared . . . . . : 03/27/2008

HMIS Information: Health- 2\* Flammability- 2  
Reactivity- 1

For specific information regarding occupational safety and health standards, please refer to the Code of Federal Regulations, Title 29, Part 1910.  
To the best of our knowledge, the information contained herein is accurate. However, neither the Tnemec Company or any of its subsidiaries assume any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown health hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist.

SHS N X YAM